

**IN THE CLAIMS:**

Please amend claims 1, 7, 10 and 16 as follows.

1. (Currently Amended) A receiving method in a receiver of a radio system, comprising:

receiving a signal with an array antenna comprising at least two antenna elements,  
oversampling the received signal,

measuring the spatial and temporal ~~colour~~ color of the received oversampled signal,

combining the received signal using combined maximum ratio combining and space-time interference rejection combining,

controlling the combining of the received signal on the basis of the measurement results.

2. (Original) The method of claim 1, further comprising:

calculating the energy of interference;

calculating the cross-correlation of noise between samples of the received signals,

calculating a threshold value as a quotient of the above values,

controlling the combining on the basis of the threshold value.

3. (Original) The method of claim 2, further comprising:

calculating at least one scaling factor as a function of the threshold value, and

controlling the combining on the basis of the scaling factor.

4. (Original) The method of claim 3, further comprising:  
calculating the scaling factor according to formula  $e^{\beta}$ , where  $\beta$  is the threshold value.

5. (Original) The method of claim 3, further comprising:  
calculating the scaling factor according to formula  $A\beta$ , where  $\beta$  is the threshold value and A is a predetermined constant.

6. (Original) The method of claim 1, further comprising:  
calculating a noise covariance matrix comprising noise variance terms, temporal covariance terms and spatial covariance terms, and  
scaling the spatial covariance terms on the basis of the measurement result.

7. (Currently Amended) The method of claim 3 ~~and 6~~, further comprising:  
scaling the spatial covariance terms using the scaling factor.

8. (Original) The method of claim 3, further comprising:  
comparing the calculated threshold value with a pre-determined value, and if the threshold value exceeds the given pre-determined value, the combining of the received signal is controlled on the basis of the scaling factor.

9. (Original) The method of claim 3, further comprising:

calculating a scaling factor for each antenna element pair separately.

10. (Currently Amended) A receiver comprising an array antenna for signal reception, the array antenna comprising at least two antenna elements, the receiver further comprising

means for oversampling the received signal,

means for measuring the spatial and temporal ~~colour~~ color of the samples

means for combining the received signal using combined maximum ratio combining and space-time interference rejection combining, and

means for controlling the combining of the received signal on the basis of the measurement result.

11. (Original) The receiver of claim 10, further comprising

means for calculating the energy of noise;

means for calculating the cross-correlation of noise between samples of the received signals,

means for calculating a threshold value as a quotient of the above values,

means for controlling the combining on the basis of the threshold value.

12. (Original) The receiver of claim 11, further comprising

means for calculating at least one scaling factor as a function of the threshold value, and controlling the combining on the basis of the scaling factor.

13. (Original) The receiver of claim 10, further comprising  
means for calculating the scaling factor according to formula  $e^{\beta}$ , where  $\beta$  is the threshold value.

14. (Original) The receiver of claim 12, further comprising  
means for calculating a noise covariance matrix comprising noise variance terms, temporal covariance terms and spatial covariance terms, and  
means for scaling the spatial covariance terms using the scaling factor.

15. (Original) The receiver of claim 12, further comprising  
means for comparing the calculated threshold value with a pre-determined value, and making the decision of the use of the scaling factor on the basis of the comparison.

16. (Currently Amended) The receiver comprising  
an array antenna for signal reception, the array antenna comprising at least two antenna elements,  
an analog to digital converter for oversampling the received signal,  
a calculator for measuring the spatial and temporal ~~colour~~ color of the samples

a calculator for combining the received signal using combined maximum ratio combining and space-time interference rejection combining, and

a calculator for controlling the combining of the received signal on the basis of the measurement result.